



## **Source Water Assessment**

## A Hydrogeologic Susceptibility and Vulnerability Assessment for Point Lay

PWSID # 320256.001

September 2004

Drinking Water Protection Program Report #1298 Alaska Department of Environmental Conservation

## Source Water Assessment for

## Point Lay

PWSID# 320256.001

September 2004

Drinking Water Protection Program Report #1298

The Drinking Water Protection Program (DWPP) is producing Source Water Assessments in compliance with the Safe Drinking Water Act Amendments of 1996. Each assessment includes a delineation of the source water area, an inventory of potential and existing contaminant sources that may impact the water, a risk ranking for each of these contaminants, and an evaluation of the potential vulnerability of these drinking water sources.

These assessments are intended to provide public water systems owners/operators, communities, and local governments with the best available information that may be used to protect the quality of their drinking water. The assessments combine information obtained from various sources, including the U.S. Environmental Protection Agency, Alaska Department of Environmental Conservation (ADEC), public water system owners/operators, and other public information sources. The results of this assessment are subject to change if additional data becomes available. It is anticipated this assessment will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of public drinking water source. If you have any additional information that may affect the results of this assessment, please contact the Program Coordinator of DWPP, (907) 269-7521.

## **CONTENTS**

SECTION  Executive Summary Drinking Water System And Area Overview Point Lay Drinking Water Protection Area Inventory of Potential and Existing Contaminant Sources Ranking of Contaminant Risks Vulnerability of the Drinking Water System	1 1 1 2 2 2 2 7
References	
TABLES	
TABLE  1. Definition of Zones 2. Susceptibility of the Water Source 3. Contaminant Risks 4. Overall Vulnerability	2 3 3 3
APPENDICES	
APPENDIX A. Point Lay Drinking Water Protection Area (Map 1)	
B. Contaminant Source Inventory and Risk Rankings (Tables 1-6)	
C. Point Lay Drinking Water Protection Area and Potential and Existing Contaminant Sources (Map 2)	
D. Vulnerability Analysis and Contaminant Risks (Charts 1 – 13)	

## Source Water Assessment for the Point Lay Water System – Lake Intake

## **Drinking Water Protection Program Alaska Department of Environmental Conservation**

#### EXECUTIVE SUMMARY

The Point Lay water system is a Class A (community) water system that obtains water from a lake approximately 1.5-miles east of the village. The intake is located at the west end of the lake and is accessible via gravel road. Access to the intake area is not restricted. The overall protection area is approximately 1 square mile in size and received a susceptibility rating of "very high". A rating of high to very high is typical for all systems with surface water intakes. Potential and existing sources of the following contaminants were evaluated for the Source Water Assessment: bacteria and viruses, nitrates and/or nitrites, heavy metals, cyanide, and other inorganic chemicals, synthetic organic chemicals, volatile organic chemicals, and other organic chemicals. Human/animal traffic along gravel roads inside the protection area and above ground fuel storage (during the summer) near the intake pump were identified as potential sources of contaminants for the drinking water source. This evaluation included all available water sampling data submitted to ADEC by the system operator. The samples may have been collected from either raw water or post-treated water. Combining the susceptibility of the surface water source with the contaminant risks, this water system has received a vulnerability rating of "medium" for all contaminant categories. This assessment can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of the community of Point Lay to protect public health.

## DRINKING WATER SYSTEM AND AREA OVERVIEW

Point Lay (Sec. 26, T005N, R045W, Umiat Meridian) is located south of the Kokolik River mouth, about 300 miles southwest of Barrow (Please see the inset of Map 1 in Appendix A for location). The current population of Point Lay is approximately 256 (ADCED, 2003). The Point Lay water system is a Class A (community) water system that utilizes water from a lake approximately 1.5-miles east of the community. The water intake is located at the west end of the lake. Access to the intake area is not restricted and is available via gravel road (See Map 1 of Appendix A).

The climate is arctic. Temperatures range from -55 to 78. Precipitation is light, averaging 6.9 inches annually, with snowfall of 21 inches. The Chukchi Sea is ice-free from late June until September (ADCED, 2003).

The 1992 Sanitary Survey indicates that storage tanks are filled once per year with water from the source lake. The survey also indicates that the intake is protected from ice buildup and siltation. Information provided by ASCG in 2004 indicates that the average daily production of the system is approximately 93,600 gallons. System operators did not provide any volume information for the lake.

A 2000 workshop on source water protection hosted by the North Slope Borough identified the following concerns regarding the current water source:

- the source lake may be receiving runoff waters from the exisiting landfill
- snowmachines may contribute oil/gas into the source waters
- dead animals may contaminate the water source

## POINT LAY DRINKING WATER PROTECTION AREA

Identifying the pathways most likely for surface contamination to reach water intake areas is the first step in determining the water system's risk. These are initially determined by looking at the drainage area contributing overland water flow to a surface water source intake. The entire drainage area is also known as the "drinking water protection area". Please refer to pages 10-11of the "Guidance Manual for Class A Public Water Systems" for additional information.

The protection area established for surface water sources by the ADEC is usually separated into three zones, limited by the watershed boundary. These zones correspond to the overland-flow distance that water travels to get to the source. The ADEC Drinking Water Protection Program's Technical Advisory Committee developed guidelines for derivation of these zones in 1998. The following is a summary of the three protection area zones:

Table 1. Definition of Zones

Definition
Areas within 1000-ft of lakes or streams
Areas within 1-mile of lakes or streams
The watershed boundary

The protection area for the Point Lay water intake includes each of these Zones although, due to the small size of the watershed, Zones B and C cover the same area (See Map 1 of Appendix A).

## INVENTORY OF POTENTIAL AND EXISTING CONTAMINANT SOURCES

The Drinking Water Protection Program has completed an inventory of potential and existing sources of contamination within the Point Lay protection area. This inventory was completed through a search of agency records and other publicly available information. There is a wide array of potential contamination sources to surface water. These contaminants are found within agricultural, residential, commercial, and industrial areas, but *can also occur within areas that have little or no development*.

For Class A public water system assessments, six categories of drinking water contaminants were inventoried. They include:

- Bacteria and viruses;
- Nitrates and/or nitrites;
- Volatile organic chemicals;
- Heavy metals, cyanide, and other inorganic chemicals;
- Synthetic Organic Chemicals; and
- Other Organic Chemicals.

Sources identified in the protection area are displayed on Map 2 of Appendix C and summarized in Table 1 of Appendix B.

#### RANKING OF CONTAMINANT RISKS

Once potential and existing sources of contamination have been identified, they are assigned a ranking according to what category and level of risk they represent. Ranking of contaminant risks for "potential" or "existing" sources of contamination is a function of the toxicity and the volume of specific contaminants associated with that source. Rankings include:

- Low;
- Medium;
- High; and
- Very High.

The time-of-travel for contaminants within the water is dependent on the physical and chemical characteristics of each contaminant. Bacteria and Viruses are only inventoried in Zone A because of their short life span. Only "Very High" and "High" rankings are inventoried within Zones B and C due to the probability of contaminant dilution by the time the contaminants reach the water intake.

The remaining tables in Appendix B (if necessary) contain the ranking of potential and existing sources of contamination with respect to bacteria and viruses, nitrates and/or nitrites, volatile organic chemicals, heavy metals, cyanide, and other inorganic chemicals, synthetic organic chemicals, and other organic chemicals.

## VULNERABILITY OF THE DRINKING WATER SYSTEM

Vulnerability of a drinking water source to contamination is a combination of two factors:

- Surface Water Susceptibility; and
- Contaminant risks.

Appendix D contains 13 charts, which together form the 'Vulnerability Analysis' for the public drinking water Source Water Assessment. Chart 1 analyzes the 'Susceptibility of the Surface Water Source' to contamination by looking at the climate, terrain, and intake location. Chart 2 analyzes 'Contaminant Risks' for the drinking water source with respect to bacteria and viruses. The 'Contaminant Risks' portion of the analysis considers potential sources of contaminants as well as a review of contamination that has or may have occurred, but has not arrived or been detected at the intake area. Chart 3 contains the 'Vulnerability Analysis for Bacteria and Viruses', which is a composite score of the Vulnerability Analysis and the overall Susceptibility. Charts 4 through 13 repeat the Contaminant Risks and Vulnerability Analyses for nitrates and nitrites, volatile organic chemicals, heavy metals, cyanide, and other inorganic chemicals, synthetic organic chemicals, and other organic chemicals, respectively.

A score for the Surface Water Susceptibility of the source is reached by considering the properties of the water intake and the surrounding area. The derivation of this information is presented below and the data for this source is shown in Chart 1 of Appendix D.

Susceptibility of the Surface Water Source – always considered to be "high" (30 points)

+

Adequate Construction of the Intake (0-5 Points)

+

Runoff Potential Within Zone B (0 - 5 Points)

+

Dilution Capacity of the Surface Water (0 – 10 Points)

=

Natural Susceptibility (0 - 50 Points)

A ranking is assigned for the Surface Water Susceptibility according to the point score:

Surface Water Source Susceptibility Ratings

40 to 50 pts Very High
30 to < 40 pts High

Table 2. Susceptibility of the Water Source

	Score	Rating
Minimum Allowable	30	
Susceptibility		
Intake Construction	0	
Adequate		
Runoff Potential	0	
Dilution Capacity	10	
Overall Susceptibility	40	Very High

For contaminants, risks to a drinking water source depend on the type, number or density, and distribution of the contaminant sources. The Contaminant Risk score has been derived from an examination of existing, and historical contamination sources that have been detected in the protection area through routine sampling. It also evaluates potential sources of contamination. Flow charts are used to assign a point score, and ratings are assigned in the same way as the susceptibility:

Contaminant Risk Ratings						
40 to 50 pts	Very High					
30 to < 40 pts	High					
20 to < 30 pts	Medium					
< 20 pts	Low					

Table 3 summarizes the Contaminant Risks for each category of drinking water contaminants.

**Table 3. Contaminant Risks** 

Category	Score	Rating
Bacteria and Viruses	12	Low
Nitrates and/or Nitrites	12	Low
Volatile Organic Chemicals	12	Low
Heavy Metals, Cyanide, and		
Other Inorganic Chemicals	12	Low
Synthetic Organic Chemicals	0	Low
Other Organic Chemicals	12	Low

Finally, an overall vulnerability score is assigned for each contaminant type by combining each of the contaminant risk scores with the susceptibility score:

Susceptibility of the Surface Water Source

$$(0-50 \text{ points})$$

+

Contaminant Risks (0 - 50 points)

=

Vulnerability of the Drinking Water Source to Contamination (0 - 100).

Again, rankings are assigned according to a point score:

Overall Vulneral	bility Ratings
80 to 100 pts	Very High
60 to < 80 pts	High
40 to < 60 pts	Medium
< 40 pts	Low

Table 4 contains the overall vulnerability scores and ratings for each of the six categories of drinking water contaminants. Note: scores are rounded off to the nearest five.

Table 4. Overall Vulnerability

Category	Score	Rating
Bacteria and Viruses	50	Medium
Nitrates and Nitrites	50	Medium
Volatile Organic Chemicals	50	Medium
Heavy Metals, Cyanide, and		
Other Inorganic Chemicals	50	Medium
Synthetic Organic Chemicals	40	Medium
Other Organic Chemicals	50	Medium

#### **Bacteria and Viruses**

The contaminant risk for bacteria and viruses is "low". Typically, coliform detection in raw water samples collected from surface water sources is normal. (See Chart 2 – Contaminant Risks for Bacteria and Viruses in Appendix D).

Coliforms (a bacteria) are found naturally in the environment and although they aren't necessarily a health threat, they are an indicator of other potentially harmful bacteria in the water, more specifically, fecal coliforms and E. coli which only come from human and animal fecal waste. Harmful bacteria can cause diarrhea, cramps, nausea, headaches, or other symptoms (EPA, 2003). Positive samples increase the overall vulnerability of the drinking water source, indicating that the source is susceptible to bacteria and virus contamination.

Positive bacteria results have not been reported in samples taken from 1999-2003.

After combining the contaminant risk for bacteria and viruses with the natural susceptibility of the source, the overall vulnerability of the source to bacteria and virus contamination is "medium".

#### **Nitrates and Nitrites**

The contaminant risk for nitrates and nitrites is "low" (See Chart 4 - Contaminant Risks for Nitrates and/or Nitrites in Appendix D). Nitrates are very mobile, moving at approximately the same rate as water.

Sampling history for the water source indicates that nitrates have been detected at levels below the MCL in samples collected from 1998 through 2003. The Maximum Contaminant Level (MCL) for nitrates is 10 milligrams per liter (mg/L). The MCL is the maximum level of contaminant that is allowed to exist in drinking water and still be consumed by humans without harmful health effects (EPA, 2003).

Possible sources of nitrates/nitrites could be from septic systems or human/animal activity along roads or trails located within the protection area.

After combining the contaminant risk for nitrates and nitrites with the natural susceptibility of the source, the overall vulnerability of the source to contamination is "medium".

#### **Volatile Organic Chemicals**

The contaminant risk for volatile organic chemicals is "low" (See Chart 6 – Contaminant Risks for Volatile Organic Chemicals in Appendix D).

Chloroform and trihalomethanes were detected at levels below the MCL during sampling in 2002-2003, although both of these chemicals typically originate during the process of water treatment and not from the source waters. The MCL for chloroform is 0.2 milligrams per liter (mg/L) and the MCL for total trihalomethanes is 0.1 mg/L.

Possible sources of volatile organic chemicals could be from human/animal activity along roads or trails located within the protection area.

After combining the contaminant risk for volatile organic chemicals with the natural susceptibility of the source, the overall vulnerability of the source to contamination is "medium".

## Heavy Metals, Cyanide, and Other Inorganic Chemicals

The contaminant risk for heavy metals is "low". Lead and copper were detected in samples collected during 2002-3 at levels above the MCL (See Chart 8 – Contaminant Risks for Heavy Metals, Cyanide, and Other Inorganic Chemicals in Appendix D). The MCL for copper is 1.3 mg/l. and the MCL for lead is 0.015 mg/l.

The most common source of these chemicals is the infrastructure of the distribution system following the treatment process and not from the source waters. Additional sources of heavy metals could be from activity along roads/trails located within the protection area.

After combining the contaminant risk for heavy metals with the natural susceptibility of the source, the overall vulnerability of the well to contamination is "medium".

#### **Synthetic Organic Chemicals**

The contaminant risk for synthetic organic chemicals is "low". After combining the contaminant risk with the natural susceptibility of the source, the overall vulnerability to synthetic organic chemicals of the source is "medium" (See Chart 11 – Contaminant Risks for Synthetic Organic Chemicals in Appendix D).

Possible sources of synthetic organic chemicals are from residential areas located within the protection area.

Ethylene dibromide was sampled for in 2002-2003, but was not detected.

#### **Other Organic Chemicals**

The contaminant risk for other organic chemicals is "low". After combining the contaminant risk with the natural susceptibility of the source, the overall vulnerability to other organic chemicals of the source is "medium" (See Chart 13 – Contaminant Risks for Other Organic Chemicals in Appendix D).

A possible source of other organic chemicals could be from human/animal activity along roads or trails located within the protection area.

Review of the historical sampling data indicates that no other organic chemicals have been sampled recently.

#### **Using the Source Water Assessment**

This assessment of contaminant risks can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of the community of Point Lay to protect public health. It is anticipated that Source Water Assessments will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of the drinking water source.


#### **REFERENCES**

 $A lask a \ Department \ of \ Community \ and \ Economic \ Development \ (ADCED), \ 2003 \ [WWW \ document]. \ URL \ http://www.dced.state.ak.us/cbd/commdb/CF\_COMDB.htm$ 

United States Environmental Protection Agency (EPA), 2003 [WWW document]. URL http://www.epa.gov/safewater/mcl.html.

## **APPENDIX A**

Point Lay
Drinking Water Protection Area Location Map
(Map 1)



## APPENDIX B

# Contaminant Source Inventory and Risk Rankings (Tables 1-6)

## Contaminant Source Inventory for NSBU - Point Lay

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Map Number	Comments
Fuel drums (above ground)	T01	T01-1	A	2	From ASCG Information (January 2004)
Highways and roads, dirt/gravel	X24	X24-1	A	2	From USGS 1:63,360 Topographic Maps

## Contaminant Source Inventory and Risk Ranking for NSBU - Point Lay Sources of Bacteria and Viruses

PWSID 320256.001

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, dirt/gravel	X24	X24-1	A	Low	2	From USGS 1:63,360 Topographic Maps

## Contaminant Source Inventory and Risk Ranking for NSBU - Point Lay

PWSID 320256.001

	•
Sources	of Nitrates/Nitrites

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, dirt/gravel	X24	X24-1	A	Low	2	From USGS 1:63,360 Topographic Maps

## Contaminant Source Inventory and Risk Ranking for NSBU - Point Lay

PWSID 320256.001

## Sources of Volatile Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Fuel drums (above ground)	T01	T01-1	A	Low	2	From ASCG Information (January 2004)
Highways and roads, dirt/gravel	X24	X24-1	A	Low	2	From USGS 1:63,360 Topographic Maps

## Contaminant Source Inventory and Risk Ranking for NSBU - Point Lay

PWSID 320256.001

## Sources of Heavy Metals, Cyanide and Other Inorganic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, dirt/gravel	X24	X24-1	A	Low	2	From USGS 1:63,360 Topographic Maps

## Contaminant Source Inventory and Risk Ranking for NSBU - Point Lay


PWSID 320256.001

## Sources of Other Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, dirt/gravel	X24	X24-1	A	Low	2	From USGS 1:63,360 Topographic Maps

## **APPENDIX C**

Point Lay
Drinking Water Protection Area
and Potential and Existing Contaminant Sources
(Map 2)



## APPENDIX D

## **Vulnerability Analysis and Contaminant Risks** (Charts 1-13)







Chart 2. Contaminant risks for Point Lay - Bacteria & Viruses






Page 3 of 24


Chart 3. Vulnerability analysis for Point Lay - Bacteria & Viruses





Page 5 of 24


Chart 4. Contaminant risks for Point Lay - Nitrates and Nitrites




Risk Levels for Nitrate/	Nitrite Sources	identified in Zoi	nes A and B	
	Zone A	Zone B	Total	
Very Highs(s)	0	0	0	
High(s)	0	0	0	
Medium(s)	0		0	
Low(s)	1		1	

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts


Matrix Score 10






Page 7 of 24


Chart 5. Vulnerability analysis for Point Lay - Nitrates and Nitrites





Page 9 of 24


Chart 6. Contaminant risks for Point Lay - Volatile Organic Chemicals




Risk Levels for VOC So	urces identified i	n Zones A and B		
	Zone A	Zone B	Total	
Very Highs(s)	0	0	0	
High(s)	0	0	0	
Medium(s)	0		0	
Low(s)	2		2	

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts


Matrix	Score	10
--------	-------	----






Page 11 of 24


Chart 7. Vulnerability analysis for Point Lay - Volatile Organic Chemicals






Page 13 of 24


#### Chart 8. Contaminant risks for Point Lay - Heavy Metals, Cyanide and Other Inorganic Chemicals




	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts


Matrix	Score		10






Page 15 of 24





Page 17 of 24


Chart 10. Contaminant risks for Point Lay - Synthetic Organic Chemicals




Risk Levels for SOC So	urces identified	in Zones A and	C	
	Zone A	Zone B	Total	
Very Highs(s)	0	0	0	
High(s)	0	0	0	
Medium(s)	0	0	0	
Low(s)	0	0	0	

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts


Matrix Score 0






Page 19 of 24


Chart 11. Vulnerability analysis for Point Lay - Synthetic Organic Chemicals





Page 21 of 24


Chart 12. Contaminant risks for Point Lay - Other Organic Chemicals




Risk Levels for OOC So	ources identified	l in Zones A and	<u>l B</u>	
	Zone A	Zone B	Total	
Very Highs(s)	0	0	0	
High(s)	0	0	0	
Medium(s)	0	0	0	
Low(s)	1	0	1	

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts

Matrix Score 10





Page 23 of 24

Chart 13. Vulnerability analysis for Point Lay - Other Organic Chemicals

