WOODY TRIHEY

## SUSITNA HYDROELECTRIC PROJECT

FEDERAL ENERGY REGULATORY COMMISSION PROJECT No. 7114

# EKLUTNA LAKE TEMPERATURE AND ICE STUDY WITH SIX MONTHS SIMULATION FOR WATANA RESERVOIR

FINAL REPORT

APRIL 1984 DOCUMENT No. 1123



ALASKA POWER AUTHORITY

Document No. 1123 Susitna File No. 42.2.2

#### SUSITNA HYDROELECTRIC PROJECT

#### EKLUTNA LAKE TEMPERATURE AND ICE STUDY (With Six Months Simulation for Watana Reservoir)

Report by

Harza-Ebasco Susitna Joint Venture

Prepared for

Alaska Power Authority

..

Final Report April 1984

## NOTICE

And a second second

.

. .

.

ANY QUESTIONS OR COMMENTS CONCERNING THIS REPORT SHOULD BE DIRECTED TO THE ALASKA POWER AUTHORITY SUSITNA PROJECT OFFICE

## TABLE OF CONTENTS

-

FIGURES

SECT	ION/TITLE	PAGE
*	LIST OF TABLES	ii
	LIST OF FIGURES	iii
1.0	INTRODUCTION	1
2.0	EKLUTNA LAKE STUDY: DYRESM MODEL CALIBRATION	1
	<ul> <li>2.1 Data Collection</li> <li>2.2 Previous Studies</li> <li>2.3 Present Study</li> <li>2.3.1 DYRESM Model Enhancements</li> <li>2.3.2 Eklutna Lake Temperature and Ice Simulation</li> </ul>	
3.0	WATANA RESERVOIR TEMPERATURE STUDY	10
	<pre>3.1 Data Collection 3.2 Previous Study 3.2.1 Reservoir Temperature Profiles 3.2.2 Outflow Temperatures</pre>	
	3.3 Present Study	
4.0	SUMMARY	13
•	REFERENCES	14
	TABLES	• 16

•

٠



### LIST OF FIGURES

NO.	TITLE
1	Eklutna Lake Location Map
2	Eklutna Lake Station Locations
3,4	Eklutna Lake Measured Weather Data
5-8	Eklutna Lake Climatic Data Availability
9-11	Eklutna Lake Observed and Predicted Temperature Profiles (Acres Results)
12,13	Eklutna Lake Outflow Temperatures (Acres Results)
14	Longwave Radiation Formula Comparison
15,24	Eklutna Lake Observed and Predicted Temperature Profiles (Harza-Ebasco Results)
25	Eklutna Lake Measured Windspeed and Outflow Temperature
26,27	Eklutna Lake Outflow Temperature (Harza-Ebasco Results)
28	Climate Stations in Upper Susitna Basin
29,30	Climatic Data Availability
31,32	Talkeetna Station Climatic Data Availability
33,34	Watana Reservoir Temperature Profiles (Acres Results)
35,36	Watana Reservoir Inflow and Outflow Temperatures (Acres Results)
37,38	Watana Reservoir Temperature Profiles (Harza-Ebasco Results)
39	Watana Reservoir Inflow and Outflow Temperatures (Harza-Ebasco Results)

-iii-

#### 1.0 INTRODUCTION

As described in the work plan of Task 42 of Susitna Hydroelectric Project, the reservoir temperature/ice studies are required for supporting the environmental studies. These studies will determine the hydrothermal behavior of the Watana and Devil Canyon reservoirs as affected by the design and operation of the project and provide necessary information for optimal design and operation of the reservoirs. It will also determine the thermal characteristics of the reservoir outflow for the downstream river temperature and ice studies and the subsequent assessment of the potential environmental impacts due to project operations. The dynamic reservoir simulation model DYRESM as developed by Imberger, Patterson and others of the University of Western Australia  $(13)\frac{1}{2}$  was selected to simulate the hydrothermal behavior of the reservoirs. To simulate the winter condition with ice formations, an ice subroutine as developed by Patterson and Hamblin for Canadian Lakes has been incorporated in the model. To calibrate the model and to verify its applicability to the Watana and Devil Canyon reservoirs under south-central and interior Alaskan climatic conditions, the Eklutna Lake study has been carried out. In this report, the results of the Eklutna Lake study and the calibration of the DYRESM model are discussed.

#### 2.0 EKLUTNA LAKE STUDY: DYRESM MODEL CALIBRATION

The DYRESM model simulates average reservoir hydrothermal behavior through parameterization of various physical processes such as inflow and outflow dynamics, mixed layer dynamics, vertical transport in the hypolimnion and surface heat and mass exchanges. The basic time increment of one day is set by the model to predict daily thermal structure. However, a smaller subdaily time increment ranging between one quarter hour and twelve hours is

1/ Refers the numbers in "Reference" at the end of text.

-1-

used to simulate the more complicated mixed layer dynamics. This procedure allows small time increments when the dynamics so require and, in less critical periods, the time increment expands without reduction in accuracy. Hence, detailed daily meteorological and hydrological data are required in the DYRESM simulation. A data collection program was established in June, 1982 for Eklutna Lake to collect data on the thermal structure of the reservoir, inflow and outflow. Eklutna Lake is located apparoximately 30 miles northeast of Anchorage (Fig. 1). A weather station (Fig. 2) located near the southern end of the lake was also established to provide the necessary meteorological data to DYRESM.

#### 2.1 Data Collection

The average daily meteorological data include:

- Mean air temperature (°C);
- Mean wind speed (m/s);
- Air vapor pressure (mb);
- Precipitation (mm);
- Cloud cover (sky fraction in tenths) or,
- Long-wave atmospheric radiation (kilojoules/m<sup>2</sup>); and
- Total short-wave radiation (insulation) (kilojoules/m<sup>2</sup>).

The six-hour averaged wind speeds along the major axis of the lake are also required to calculate the internal mixing due to internal waves.

In addition to meteorological data, the quantity and temperature of inflow to the lake and outflow from the lake are required to simulate the reservoir dynamics (1). The inflow data including temperature and stage was obtained by establishing two gaging stations on the major tributaries, East Fork and Glacier Fork (Fig. 2) (1). For calibrating the DYRESM model, measurements of lake temperature profiles were made at seven locations on an approximate two-week interval (1). Detailed descriptions of the input data collection program are given by R&M (11). The quantity and temperature of the daily outflow through the Eklutna Hydroelectric plant turbines were furnished by the Alaska Power Administration of the U.S. Dept. of Energy.

These data have been collected, reduced, compiled, and reported by the R&M Consultants, Inc. (3, 11). The monitoring system and the accuracy of the measurements were also described by R&M (1, 3, 11). The data collection program began in June, 1982 and will be terminated in early 1984. Periodic malfunctioning of instruments have been experienced, especially in July and August of 1982 where many days of data are not recorded (11), and consequently, estimations of these data were required based on nearby stations at Palmer and Anchorage. The ice thickness measurements were taken approximately once a month.

A comparison of the relative humidities measured at Anchorage and Talkeetna by the National Oceanic and Atmospheric Administration (NOAA) indicates that the Eklutna relative humidity data are generally too low and are not in good agreement with other climatic (especially precipitation) data measured at Eklutna Lake Station. Therefore, the Anchorage relative humidities published by NOAA were used to compute the vapor pressures.

The data records available at Eklutna Lake station are plotted and shown on Figs. 3 and 4. The period of recorded data at the Eklutna Lake Station are shown in Figs. 5-8.

#### 2.2 Previous Studies

A previous effort by ACRES on the calibration and verification of the DYRESM model with the observed data had concentrated on the period of June, 1982 through December, 1982 during which the field data were measured.

-3-

Adjustments were made on all wind speed data. In DYRESM, the wind speeds are assumed to be measured at a height of six meters while the field instrument measures wind speed at about two meters above surrounding scrub vegetation. Therefore, the wind speeds were corrected based on the velocity distribution in the boundary layer of the air current. The adjustment produces an increase of 17 percent in measured wind speeds.

It was noted that the July and August field measurements were quite incomplete, as shown in Fig. 6, and significant amounts of meteorological data had to be estimated (12). Therefore, the Eklutna Lake temperature/ice simulation was made for the periods June 1 to August 25, 1982 and August 25 to December 31, 1982 to minimize the effect of data gap (14). However, as described later concerning the current study, satisfactory results have been obtained with continuous simulation from June 1, 1982 to December 31, 1982.

The simulated temperature profiles did show reasonable agreement with the measured temperatures except under severe wind conditions such as the high wind periods which occured between September 9 and September 21. Under severe wind condition, significant mixing can occur and warmer water can be In addition, the one-dimensionality of the expected in the hypolimnion. reservoir hydrothermal behavior is not strictly valid. Improved agreement was obtained by increasing the vertical diffusion coefficient, which represents the efficiency of the transport of mass and momentum, from 0.048 to 0.096 based on the Wedderburn number criterion (13, 14). The Wedderburn number characterizes the one-dimensionality of the reservoir dynamics. When this number has a value less than 3 a departure from the one-dimensional assumption is indicated. The high wind condition is later treated with the concept of equivalent epilimnion deepening and the corrections based on the Wedderburn criteria are no longer applied.

The principal constants used in the DYRESM simulation are given in Table 1. These constants are related to well identified physical processes and are determined from experimental or field data (13, 14). The simulated and

-4-

measured temperature profiles at Station 9 in the approximate center of the lake are given in Figs. 9 to 11. In general, most profiles are modeled to within 0.5°C with few exceptions where the difference was up to about 2°C.

The simulated and measured outflow temperature of the Eklutna Lake are given in Figs. 12 and 13. The predicted outflow temperature is, in general, 1 to 2°C below measured temperature during the period of July to mid-September. From mid-September to December, the predicted and measured temperatures match relatively well. Further improvement of the simulation have been made and are discussed in section 2.3. It includes upgrading the vapor pressure and long wave radiation calculations and taking into account the surface wind effects. The simulation also indicates that the ice-cover formation will begin in mid-November and that 21 inches of ice-cover will exist near the end of December. On January 13, 1983, an ice-cover of about 16 inches was measured near the center of the lake. Hence, the simulation appears to overestimate the ice-cover thickness by about 5 inches in early January 1983. However, the ice model used in the present study yields much improved predictions and they are described in the following sections.

#### 2.3 Present Study

#### 2.3.1 DYRESM Model Enhancements

The Eklutna Lake temperature and ice analyses conducted in the previous study indicate that the DYRESM model performs relatively well in duplicating the average field condition of the lake thermal structure. However, upon further examination of the previous results, field data, and the configuration of the intake structure, several enhancements and/or modifications of the DYRESM model were made and they are discussed as follows:

The "Swinbank" equation used in the DYRESM model may be significantly underestimating the incoming long wave atmospheric radiation on the Lake. Such observation was made independently by both Dr. P.F. Hamblin, the consultant

-5-

to the reservoir temperature and ice study, and R&M. Additional analyses indicate that the empirical equation given by Anderson (4) agrees well with the measured values at Watana and was incorporated in the DYRESM model (Fig. 14). The Anderson's equation is given as

 $H_{L.W.} = E_a \sigma T^4$ 

where  $H_{L.W.}$  is the long-wave atmospheric radiation (KJ/day),  $E_a$  is the atmospheric emissivity,  $\sigma$  is the Stephen Boltzman constant (4.979 x  $10^{-6}$  KJ/day), and T is the air temperature (° Kelvin). The atmospheric emissivity is dependent upon the cloudiness of the sky and the relative humidity or vapor pressure (3). The emissivity increases as the cloud cover or vapor pressure increases.

Using the Anderson's equation, closer matches to measured temperature profiles taken near the center of the lake (Station 9) were obtained as shown in Figs. 15 to 24.

With regard to outflow temperature predictions there are two modifications. One for the geometry of the intake structure and the other for wind forcing The local bathymetric condition and the configuration of the ineffects. take structure are quite different from the conditions assumed in the DYRESM model. The model assumes that a vertical wall such as a dam is located at the downstream end of the reservoir and the offtakes are located at the center of the dam width. However, the intake structure of the Eklutna powerhouse is located near the north end of the lake on a mild sloping bottom and resembles a horizontal outfall structure situated on an excavated area. Hence, the Eklutna intake may draw most of the water from the layers With the combined effects of the sloping bottom, the horizontal above. outfall type intake and the local excavation, the outflow temperature may not be treated accordingly by theory. The wind effect, especially in the months of July, August and September, is clearly shown in the outflow temperature and 6-hr wind plots, given in Fig. 25. It is understood that such

-6-

outflow thermal behavior has also been observed by the powerhouse personnel. When a downlake wind (toward the intake area) occurs, a warmer than normal outflow temperature is observed. Such temporal deviation of the outflow temperature from its normal trend can be attributed to not only the surface wind shear stress but also the behavior of the internal waves of the stratified fluid, the depth of the epilimnion, the relative position of the intake to the thermocline and the local bathymetric configuration. Since the present time frame does not permit further development of the DYRESM model to take into account all the variables identified above, only the surface wind and the bottom effects are considered in the current study and are discussed as follows:

The bathymetric information indicates that the bottom slope near the intake area is about 1 vertical to 100 horizontal. Hence, the withdrawal layer (outflow) distribution must be modified in the outflow dynamics calculation. Through several numerical experiments, it was found that satisfactory outflow temperatures can be obtained by assuming that the offtake draws water mainly from layers above the intake and the withdrawal from the lower layers is insignificant.

The strong downlake winds tend to increase the mixing locally near the intake. The strength of such wind induced mixing is considered proportional to the magnitude of the wind along the major axis of the lake toward the intake. The effect is considered equivalent to the deepening of the epilimnion at the intake area. The equivalent deepening of the epilimnion  $\Delta$ H is computed by the following emperical equation:

$$\Delta H$$
 = (Intake depth) x  $\frac{W}{C1}$  x [(1 -  $\frac{W}{C1}$ ) x C2]<sup>2</sup>

Where W is the 6-hr wind in the downlake direction and Cl and C2 are empirical constants for adjusting the magnitude of the responses. It was found that values of 20.0 and 0.25 for Cl and C2 respectively produce satisfactory results for summer, and 7.5 and 0.25 for fall. Since better agreements were

-7-

obtained with these modifications, the adjustments based on Wedderburn criteria for high wind condition as described previously were not applied and a constant vertical diffusion coefficient of 0.048 was used.

The influence of ice and snow on the heat transfer across the water surface of a reservoir is taken into account by simulating the percentage of snow and ice cover and their thickness as a function of time. The effect of snow and ice is to reduce the amount of short wave radiation reaching the upper layers of the reservoir through the absorptive properties of ice and snow and to reduce the cooling of the reservoir surface that would otherwise occur by providing a covering layer of reduced thermal conductivity and by creating additional ice at the ice-water boundary.

Specific physical processes incorporated into the model of ice and snow are:

- 1. Minimum ice thickness of 10 cm.
- Surface melting of either snow or ice as well as ice melting at the ice water interface.
- 3. Reduction of snow or ice thickness by surface evaporation
- 4. Effect of surface vapor pressure on ice or snow
- 5. Snow albedo as a function of snow age and temperature
- 6. Short wave absorption in snow and ice
- 7. Ice-water heat flux due to molecular conduction across ice-water interface plus turbulent sensible heat flux due to inflow and outflow induced current in the upper layer of the reservoir.
- 8. Computation of surface temperature of the snow or ice from the surface heat budget.
- Limitation of maximum snow thickness allowable based on ice buoyancy relative to snow loading
- 10. Incorporation of frazil ice input to total ice volume in the reservoir

-8-

#### 2.3.2 Eklutna Lake Temperature and Ice Simulation

One of the major objectives in the Eklutna Lake calibration study is to develop an understanding of the capability, concept, and structure of the DYRESM Model. This understanding has led to the development of several program enhancements to calibrate the model under south-central and interior Alaskan climatic conditions as previously discussed. The Eklutna Lake study has also demonstrated the need for accurate climatic data to enable the model to properly simulate the hydrothermal behavior of the reservoirs. Every effort should be made in the future to insure the accuracy and reliability of field measurement instruments and data collection procedures.

The study by Harza-Ebasco (H/E) considered the period of June, 1982 through June, 1983. The H/E simulation also included a 17% increase in measured windspeeds to correct the velocity to the height above vegetation assumed by the model. The Wedderburn number modification procedure was not used in lieu of the empirical equation to deepen the epiliminion at the intake area and the modification of the withdrawal dynamics.

The results of the H/E Eklutna Lake study are shown in the temperature profile plots, Figs. 15 to 24, and in the outflow temperature time history plots, Figs. 26 and 27. The results of the study demonstrate the capability for the DYRESM Model to properly simulate the hydrothermal behavior of a reservoir in the specific region of the Susitna Project. The results show the accurate prediction of winter outflow temperatures within a tolerance of less than  $\pm$  1 degree Celcius. The results also show that the summer outflow temperatures were simulated to within about  $\pm$  1 degree Celcius. However, temporal deviations of up to about  $\pm$  2 degrees Celcius have also occasionally occured, especially during and after high wind periods. The surface wind shear effects and the internal wave motions near the intake structure are extremely difficult to model with a one-dimensional approach and threedimensional modeling is not considered practical at this time. The outflow temperature is a principle input parameter for the river temperature, and

-9-

river ice studies being undertaken to determine project effects on existing thermal regime of the Susitna River. The results also show an excellent correspondence between measured ice thickness and predicted ice thickness except for one point in March at Station 13 which is located near the north end of the lake. There were no ice measurements made near the center of the lake in March. The relatively thick ice measured at Station 13 in March may be considered due to local accumulation of snow caused by downlake winds. Therefore, the larger difference (Fig. 27) shown in March is not considered as a major concern.

It is understood that the Eklutna Lake reservoir data collection program will be terminated in 1984. The additional data collected and compiled by R&M will then be available to extend the Eklutna Lake temperature simulation. The results from that study will be reported as a supplement to this report.

#### 3.0 WATANA RESERVOIR TEMPERATURE STUDY

The DYRESM model was used to simulate Watana reservoir temperature behavior and outlet temperatures under the 1981 flow condition. The parameter values of the model used in the Eklutna Lake calibration have been applied. A field program was established in April, 1980 within the Susitna River Basin (Watana Camp) to collect meteorological data (5-12) for the DYRESM model. The climatic stations are shown in Fig. 28.

#### 3.1 Data Collection

The required average daily meteorological data include:

- Mean air temperature (°C);
- Mean wind speed (m/s);
- Air vapor pressure (mb);
- Precipitation (mm);

-10-

- Long-wave radiation  $(KJ/m^2)$  or cloud cover (sky fraction in tenths); and
- Total short-wave radiation  $(KJ/m^2)$ .

The periods of the available records are shown in Figs. 29-32.

#### 3.2 Previous Study

As described in the License Application, daily simulations were made by Acres to predict the thermal behavior of the Watana reservoir operating under Case C power operation condition (12,000 cfs minimum August flow). The simulation period is six months (June 1 through December 31, 1981).

#### 3.2.1 Reservoir Temperature Profiles

The simulated temperature profiles for the first day of each month from June through December 1981 are shown in Figs. 33 and 34. Stratification occurs during June, July and August. The maximum surface temperature simulated was 10.9°C on July 3 and August 28. Cooling in September results in the gradual destruction of summer stratification and the deepening of the epiliminion. The process continues until isothermal conditions occur in late October. Isothermal conditions continue until water reaches its maximum density, after which reverse stratification takes place. A weak stratification occurs in late November and remains relatively stable throughout December. A full ice cover occurs on November 22. Ice thickness on December 31 was predicted at 31 inches by the model (14).

#### 3.2.2 Outflow Temperatures

The multiple-level intake at Watana allows the utility to provide variable water temperatures within a range dictated by the thermal structure within the reservoir. The philosophy of operating this structure is to provide water temperatures as close to the ambient river temperatures as possible.

-11-

In general, this results in the intake closest to the surface being used, provided hydraulic submergence criteria are met. However, on a few days, deeper intakes are used to provide water temperatures which are closer to those required. The simulated outflow temperatures are shown in Figs. 35 and 36.

The comparison of natural temperature and simulated outflow temperature shows that during summer months, the outflow temperature follows natural temperature trends but is cooler during July and slightly warmer in August. During September to mid-November, the results show a gradual reduction of outflow temperature from 9.5°C to 2°C while the inflow temperature drops much sooner to 0.5°C in mid-September. Stable outflow temperature of around 2°C start in mid-November and continue throughout December.

#### 3.3 Present Study

The input data used in the previous study and the parameter values of the model used in the calibration study were used to simulate reservoir temperature profiles and outflow temperatures. The selective withdrawal capability which was not required in Eklutna Lake Study was implemented to simulate operation of the multi-level intakes.

The simulated temperature profiles and outflow temperatures are shown in Figs. 37, 38 and 39. The results indicate that the temperature profiles obtained in the two studies are relatively similar, and the difference in outflow temperatures between the two studies are within 0.5°C (average). Both studies also predicted an increase of about 6°C in the stream flow temperature in late September due to discharging of warmer stratified water from the reservoir. A full ice cover occurs on December 1, 10 days later than the previous study. Ice thickness on December 31 was estimated about 25 inches, 6 inches less than the previous study. Since the ice and snow model yielded better results in the Eklutna Lake Study, the results obtained in the present Watana Study are also considered more accurate.

#### 4.0 SUMMARY

In this study we have simulated the Eklutna Lake thermal behavior and ice growth based on the DYRESM Model. Some of the input data have been improved for consistency with the nearby climatic stations. The outflow dynamics have also been modified to take into account the special configuration of the horizontal intake structure, the mild sloping bottom, and the wind forcing effect. All modifications made to the model for the Eklutna Lake study are not necessarily required for the Watana and Devil Canyon reservoir studies. Both reservoirs will have vertical multi-level power intake structures with approach channels. The approach channels will force the intakes to withdraw more water from the upper layers, therefore, the outflow algorithm has been modified to accomodate such effects. The longwave radiation formula presented by Anderson will be used in the Susitna Reservoir Studies as this equation seems to better apply to the project The modifications made to the ice and snow processes will also location. remain and others may be added to better model the effects of incoming frazil ice upon the total ice volume in the reservoir.

The results of the Eklutna Lake study establishes the applicability of the DYRESM model to accurately simulate thermal reservoir processes in the South-Central Alaskan climatic conditions.

The resulting DYRESM model calibrated through the Eklutna Lake Study is assumed to be applicable to Watana reservoir with minor modifications to take into account the effects of approach channels and frazil ice inflows. The parameter values of the Eklutna model were used to simulate Watana reservoir temperature profiles and outflow temperatures. The study is believed to yield improved results as compared with Acres'.

-13-



### REFERENCES

.

•

0.	TITLES
Þ	R & M Consultants Incorporated, "Susitna Hydroelectric Project, Glacia Lake Studies," prepared for Acres American Incorporated and Alask Power Authority, December, 1982.
•	R & M Consultants Incorporated, "Susitna Hydroelectric Project, DYRES Input Data," prepared for Harza-Ebasco Susitna Joint Venture an Alaska Power Authority, August, 1983.
•	J.M. Raphael, "Prediction of Temperature in Rivers and Reservoirs," Proc., ASCE, J. Power Div., PO2, July, 1962.
•	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 1 - Susitna Glacier Station," prepared for Alaska Power Authority, December, 1982.
•	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 2 - Denali Station," prepared for Alaska Power Authority, December, 1982.
•	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 3 - Tyone River Station," prepare for Alaska Power Authority, December, 1982.
•	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 4 - Kosina Creek Station, prepared for Alaska Power Authority, December, 1982.
•	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 5 - Watana Station," prepared fo Alaska Power Authority, December, 1982.
•	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 6 - Devil Canyon Station, prepared for Alaska Power Authority, December, 1982.
0.	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 7 - Sherman Station," prepared fo Alaska Power Authority, December 1982.
l.	R & M Consultants Incorporated, "Susitna Hydroelectric Project Processed Climatic Data, Volume 8 - Eklutna Lake Station, prepared for Alaska Power Authority December 1982

-14-

#### REFERENCES (cont'd)

NO.	TITLES

- 12. R & M Consultants Incorporated, "Susitna Hydroelectric Project, Field Data Collection and Processing, Supplement 1," prepared for Alaska Power Authority, December, 1982.
- 13. J. Imberger, and J.C. Patterson, "A Dynamic Reservoir Simulation Model - DYRESM:5," Transport Models for Inland and Coastal Waters, Chapter 9, Academic Press, 1981.
- 14. Acres American Incorporated, "Susitna Hydroelectric Project, Feasibility Report - Supplement: Chapter 8," prepared for Alaska Power Authority, 1983.



ſ

[

Γ

## TABLE 1 - DYRESM Parameters for Eklutna Lake

0.

 $\bigcirc$ 

PARAMETER	VALUE
Convective overturn, CK	0.125
Mechanical stirring (wind), ETA	1.230
Temporal surface wind or cooling effects, CT	0.510
Shear production for entrainment, CS	0.200
Shear instability, AKH	0.300
Diffusion constant for hypolimnetic mixing	0.048
Drag coefficient of river inflow	0.015

•

.



[







EKLUTNA LAKE LOCATION MAP

HARZA-EBASCO Susitna Joint Venture • January 1984

 $\left[\right]$ 

 $\square$ 



Station Moorings 1

Weather Station Θ

00

Δ

Stream Gauge

EKLUTNA LAKE STATION LOCATIONS

NORTH

HARZA-EBASCO Susitna Joint Venture • January 1984





Z				198	2		
ATI	METEOROLOGICAL AND	JANUARY	FEBRUARY	MARCH	APRIL	MAY	JUNE
s	STREAM FLOW DATA	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25
	SHORT WAVE RADIATION						
	SKY COVER						
	WIND SPEED						
ų	PRECIPITATION						
Ś	RELATIVE HUMIDITY						
INA	3-HOUR WIND SPEED						
CLU.	OUTFLOW AND TEMPERATURE						
Ť.	LAKE LEVEL						
	INFLOWS AND TEMPERATURE						
	• East Fork						
	Glacier Fork						
	• Others						
	SHORT WAVE RADIATION						
	SKY COVER			i kana ang kana kana kana kana kana kana			
AGE			I DER DER GER STOLEN IST UND DER GER 1 Einen der Gertreiten Stade songen borgen	I DE LA LANGA DE LA LANGE DE LA LANGE DE LANGE 1999 - DE LA LANGE DE LA LANGE DE LA LANGE DE LA LANGE DE LA LA			
НОН	WIND SPEED			I FALLA LA SOL REFOL FOLGET ENDER PORTAL E de la la sol refol e trest ender provi i			arnan kultu kultu ila kultu kultu ku
ANC	PRECIPITATION			a 1964 in 1966 and 1997 and 1998 and 1998 Salah seberahan seberahan seberahan seberah		I MANUN ANDER NUTAL DEMONSTRATE DE LA DEL DE LA DEL	den in Salah (dalah kerupakén berak Banan salah kerupakén berak
				i të ba dha Millan Soket e jatë pikëti. 1969 ji dha marke të bat obarta në bat			i i a la su
	3-HOUR WIND SPEED			I ATTEL CALLER HARMALI DE LE BRER I DE DE LE Break de le complete de le complete de le complete de la complete de la complete de la complete de la complete d			
	·						

Z				19	982		
IF	METEOROLOGICAL AND	JULY	AUGUST	SEPTEMBER	OCTOBER	NOVEMBER	DECEMBER
<u></u>	STREAM FLOW DATA	5 10 15 20 25 30	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30
	SHORTWAVE RADIATION						
	SKY COVER						
	WIND SPEED						
Ш Ш	PRECIPITATION						
Ň	RELATIVE HUMIDITY						
TNA	3-HOUR WIND SPEED						
KLU K	OUTFLOW AND TEMPERATURE						
Ē	LAKE LEVEL						
	INFLOWS AND TEMPERATURE						
	• East Fork						
	• Glacier Fork						
	• Others		k put senes seven prove a presentation a 1996: Letter cover prove seven a second			I FARE EL DE L'ALLE EL DE LE DE LE	
	SHORTWAVE RADIATION	I DE LE PERI ILIER MET LEVE LEVE ILEVE (1966) Le periode de leve leve de leve de leve	NI NGU ULATA SUBSU LOKU MUMU ANALA ANALA. Na ngu ulata subsu kanala mumu anala s	ISAACAA KUUNANA KUUNAN	i Jaha Kasa Ingga Kasa Kasa Kasa Kasa Kasa Kasa Kasa K	REAL PROPERTY OF THE PROPERTY OF T	
	SKY COVER		NE MAR DE LITE DE LA GUARDA DE LA SUL PEDE Region contro de la contro de la sul de la sul		I NA MANANANA MANANA		
A GE	AIR TEMPERATURE		NERON DE LE L'ANDER LANDER DE LANDER DE LANDER DE Refere de l'Anne de la des la des de lander de	***************************************	INGRA LALIA DAGA KANASANG MUNANANAN Ing kana dagan panga kanasang	, FRANKER E BERNERE E Bernere e Bernere e B	
ЮН	WIND SPEED				I NARAH KUTAN KUTAN KUTAN KUTAN KUTAN Kutan denga kutan kutan kutan kutan k	I DE LA EL DE LA LA DELLA LA D I DE LA DELLA	
ANC	PRECIPITATION						
	RELATIVE HUMIDITY						
	3-HOUR WIND SPEED		E TA BE CONCERNENCE NO DE LA CONTRE DE LA CONTRE D E FRANCES DE LA CONCERNENCE DE LA CONTRE DE LA				

S				194	B <b>3</b>		
ATI	METEOROLOGICAL AND	JANUARY	FEBRUARY	MARCH	APRIL	MAY	JUNE
-IS		5 10 15 20 25 30			5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25
	AIR TEMPERATURE						
	WIND SPEED						
Ш	PRECIPITATION						
۲							
TNA	3-HOUR WIND SPEED						
Ę	OUTFLOW AND TEMPERATURE	امر واحد المارية بين المراجع في المراجع المراجع المراجع (1999). 1993 - مراجع مراجع المراجع (1999). 1993 - مراجع مراجع (1999).					
Ξ	LAKE LEVEL						ne pra pra po
	INFLOWS AND TEMPERATURE						
	• East Fork						
	Glacier Fork					I FARALANDA ANGLI DOGGA DOGU DALANG. 13560 GATAGANGA BAGA BAGA MANANAN	ada u da con la constanta da la constanta Norma senta constanta da Canada da const
	• Others						
	SHORTWAVE RADIATION						
	SKY COVER						
AGE	AIR TEMPERATURE			ANTER CONTRACTOR CONT			
10R	WIND SPEED						
NC	PRECIPITATION						
٩	RELATIVE HUMIDITY						
	3-HOUR WIND SPEED						

.

5

N				, 19	83		
ATI	METEOROLOGICAL AND	JULY	AUGUST	SEPTEMBER	OCTOBER	NOVEMBER	DECEMBER
ร	STREAM FLOW DATA	5 10 15 20 25 30	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30
	SHORT WAVE RADIATION						
	SKY COVER						
	WIND SPEED	adalah kabén seri di karé da séri di karé da karé da séri di karé da séri di karé da séri di karé da séri di k Salah salah salah séri di karé da séri di karé d					
ų	PRECIPITATION						
Ŝ	RELATIVE HUMIDITY						
AN	3-HOUR WIND SPEED				LE LE LE DEREN FRANKLIK DEREN KUNNEL DER BERUFF		
LU LU	OUTFLOW AND TEMPERATURE	a sera a real a real de la sera de	teri i saca pana taset na i i i i i		a de la la sel de la La sel de la		
Ť	LAKE LEVEL	ARCHARDON DE LA LA CALLEN DE LA	NATUR SANA MUTA DANA DALA SULA SULA.		n na mana ang ang ang ang ang ang ang ang ang		
	INFLOWS AND TEMPERATURE						
	• East Fork 🛛						
	Glacier Fork	ARRENT DALLAN DALLAN DE ANG DALLAN					
	• Others						
	SHORT WAVE RADIATION						
	SKY COVER						
AGE	AIR TEMPERATURE						
10R	WIND SPEED						
NC NC	PRECIPITATION						
٩	RELATIVE HUMIDITY						
	3-HOUR WIND SPEED						
İ							
İ							
		Management     M					

4









÷.

# EKLUTNA LAKE RESERVOIR TEMPREATURE SIMULATION JUNE / SEPTEMBER



EKLUTNA LAKE RESERVOIR TEMPERATURE SIMULATION OCTOBER / DECEMBER

(Acres Study, 1982-1983)



















. . . . . . . . .





· · · · · · · · · · · ·









CLIMATIC STATIONS IN UPPER SUSITNA BASIN

HARZA-EBASCO Susitna Joint Venture • January 1984

Z				198	31		
ТАТІ		JANUARY	FEBRUARY	MARCH	APRIL	MAY	JUNE
	SKY COVER						
ANA	WIND SPEED						
WAT	PRECIPITATION						
	SKY COVER						
ЧОХ	AIR TEMPERATURE						
CAN	WIND SPEED						
۲۲ ۲	PRECIPITATION						
DE	RELATIVE HUMIDITY						
	3-HOUR WIND SPEED						
	SHORT WAVE RADIATION						
	SKY COVER						
∢	AIR TEMPERATURE						
NIS	WIND SPEED						
¥	PRECIPITATION						
	RELATIVE HUMIDITY						
	3-HOUR WIND SPEED						

NO				198	1		
TAT		JULY	AUGUST	SEPTEMBER	OCTOBER	NOVEMBER	DECEMBER
<u>ن</u>				5 10 15 20 25			5 10 15 20 25 30
	SKT COVER						
ANA							
IAT.							
5	PRECIPITATION						
	3-HOUR WIND SPEED						
	SHORT WAVE RADIATION						a de la la company de la company de la company de la company de la company de la company de la company de la co La company de la company de
z	SKY COVER						
× Z	AIR TEMPERATURE						R C C C C C C C C C C C C C C C C C C C
S	WIND SPEED						
<u></u>	PRECIPITATION						
ă	RELATIVE HUMIDITY						
	3-HOUR WIND SPEED						
	SHORT WAVE RADIATION						
	SKY COVER						
<	AIR TEMPERATURE						
SIN	WIND SPEED						
¥	PRECIPITATION						
	RELATIVE HUMIDITY						
	3-HOUR WIND SPEED						
	· · · · · · ·						

P

Х О				19	81	, , , , , , , , , , , , , , , , , , ,	
таті		JANUARY	FEBRUARY	MARCH	APRIL	MAY	JUNE
ŝ		5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25
	SKY COVED						
₹			NATURA DE TRA PARA DE LA CALA	NARAN AND PANARAN TANAN ATAMA ATAMA Kaleh kerangan kanan basan basa	i na pri a degli paga i prev franci propul I na pri addini addini addini pri pri	Langa burga pilan pinen suna-suna- Kanan berini baban baran burga sugar	
Ē			<b>Mana kana kana kana a</b>			New Pier and a state to a state of the	Neess Law 71 Pares Prove Departments Barel Kalika Jahos Bares Bares Bares
LK.			RANKA UNCU UNCU NA CALANA ANA ANA ANA				tenel table (1504 tene) is her suser Sectation is en burget stigt side
4			MALAN MALAN ( <b>) FEA FIGH</b> A ( ) AND ( ) AND			i farta da se contra por la da se la da se contra d Se contra da se contra d	Januar sendi kanılı dener teksi sənər Dəsili ini ini den bi beriki dələti ini ini
					NA BER SERA I DAVIE PARKE BREES BREE Seren anset and ber seren brees	i pocas la più piatri picki picch previ I pocas la più picchi picki picchi previ	CERTE PROVE STARE DUDIN VEDAR STAR. Marke Brand Stare Black Brigs (2003)
	J-HOON WIND SPEED						Senera sena popular population da este provi Principal de la constant de la constant de la constant de la constant de la constant de la constant de la const
ļ							
ŀ							
I							
	3						
ŀ							
l							
ŀ							
	<u>~</u>						
ŀ							

Z O		1981					
TATI		JULY	AUGUST	SEPTEMBER	OCTOBER	NOVEMBER	DECEMBER
Ś		5 10 15 20 25 30	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30	5 10 15 20 25	5 10 15 20 25 30
TALKEETNA	SHORT WAVE RADIATION						
		I FIEL MARTINESS STATE TO A SUBMIT					
							17695 DE BET DEBEN SAN DE DE DE SA SU DE SA 11611 DE DE DEBEN DE DE DE DE DE DE DE DE
	PRECIPITATION						
	3-HOUR WINO SPEED						
	· · · · · · · · · · · · · · · · · · ·						
	·						

•

•

÷

==== ELEVATION (FEET) LEGEND: - JUNE I, 1981 \_ - JULY I, 1981 - AUGUST 1, 1981 I WATER TEMPERATURE (°C) NOTE: TEMPERATURE PROFILES SIMULATED USING 1981 DATA. (CASE C) WATANA RESERVOIR TEMPERATURE PROFILES JUNE / AUGUST (Acres)

Figure 34 2200 1 2150 2100 2050 I ELEVATION (FEET) 0 0 3 ٦ 1 1950 1 1900 :| LEGEND: - SEPTEMBER 1, 1981 \_ 1850 OCTOBER 1, 1981 NOVEMBER I, 1981 -DECEMBERI, 1981 DECEMBER 31, 1981 1800 -1750 2 3 4 5 7 8 9 10 П I 6 12 WATER TEMPERATURE (°C) NOTE: TEMPERATURE PROFILES SIMULATED USING 1981 DATA. (CASE C)

WATANA RESERVOIR TEMPERATURE PROFILES SEPTEMBER / DECEMBER (Acres)



WATANA RESERVOIR INFLOW AND OUTFLOW TEMPERATURES JUNE / SEPTEMBER



.

WATANA RESERVOIR INFLOW AND OUTFLOW TEMPERATURES OCTOBER / DECEMBER





